

How to use magic chef dishwasher

(Refer to Figure 12.) Carefully empty filter and replace into position once clean. The benefits of registering your product update. Registering your product will allow for more efficient warranty service processing when warranty service is required. Registering your product could act as your proof of purchase in the event of insurance loss. Regularly wipe the door and control panel with this appliance. 1. DO NOT use this appliance for other than its intended use. 2. DO NOT unplug your appliance by pulling on the power cord. Quick Connect Connectione. d/b/a MC Appliance Corporation. All rights reserved. Try another brand. Never use any other cleaner than dishwasher detergent for the risk of foaming or suds. Rust stains on cutlery Cutlery is not corro-sion resistant. Only put corrosion resistant items in the dishwasher. A program was not run after dishwasher detergent was added. Traces of detergent was added. Traces of detergent have gotten into the wash cycle. Run the dishwasher after adding dishwasher adding dishwasher after adding dishwasher adding dishwasher adding dishwasher add the items which are obstructing the spray arm. If you are unable to interrupt the program, fix the spray arm position after cycle is complete. Rattling noise in the wash cabinetItem inside is loose. If you are able to, interrupt the program and rearrange items in the dishwasher. Knocking noise in the water pipesThis may be caused byon-site installation orthe cross-section of the piping. This has no influence on dishwasher function. If in doubt, contact a suitably plumber. Unsatisfactory Washing The dishes are not clean Improper wash program selected. Select a more intensive program. To remove items caught by this filter, please see section entitled "Filter Assembly System" below.c. Main Filter: Food and soil particles trapped by this filter are pulverized by a special jet on the spray arm and washed down to drain. bacFor best performance and results, the filter must be cleaned regularly. NOTE: Only use branded rinse aid for dishwasher. Pause IndicatorPower Button: Used to turn the unit on and off. Pressagain to resume running the unit.LOADING THE DISHWASHERBe sure that the dishwasher is sitting on a surface that will not be affected by its weight of, close to the sink with the drain hose properly connected and set to drain. Scrape off any large amounts of leftover food. Coarse Filter: Larger items that could block the drain are trapped in the coarse filter. This warranty gives you specific legal rights. WARNING: DO NOT use an extension cord or an adaptor plug with this appliance. The dishwasher should be placed near the water supply (faucet) and a sink for draining, as well as a properly installed and grounded electrical outlet. Generally, only one tablespoon of detergent is needed for a normal wash load, though more heavily soiled items may need more detergent is needed for a normal wash load, though more heavily soiled items may need more detergent is needed for a normal wash load, though more heavily soiled items may need more detergent. heater element, located in the sump underneath the removable filter screen. Faucet Adapter Connectionl. Be sure to keep the sink clean and do not immerse the drainage hose in water to prevent sewage from flowing back. Fill the dispenser to required level based on washing cycle. Fill the detergent dispenser with detergent. Repeat if necessary. Spilled Rinse Aid. Drain Port Connectiond. The smaller compartment on the left side (Figure 8, a) is for 0.50oz (15g) of detergent, and the larger compartment on the right side (Figure 8, b) holds 0.88oz (25g). Place the unit in a box and store it in a cool, dry location. DO NOT wrap the power cord tightly around the appliance or put any pressure on the power cord when storage to avoid damaging the power cord. TROUBLESHOOTINGLimited WarrantyMC Appliance Corporation warrants each new Compact Refrigerator to be free from defects in material and workmanship, and agrees to remedy any such defect or to furnish new parts), at the company's option, for any parts) of the unit that has failed during the warranty period. When disposing of or removing from service, be sure to remove the door from the front of the unit.18. You may be able to correct it yourself. Clean the spray arm jets. ALWAYS be sure to push the drain hose in place correctly and that the connection is secure (Fig. NOTE: The entire filter assembly should be cleaned at least once. A WARNING: Never run the dishwasher without the filters in place, and you may also have other rights that vary from state to state. REFERENCE LINK 1PLEASE READ THIS MANUAL CAREFULLY BEFORE USING YOUR DISHWASHER AND KEEP IT FOR FUTURE REFERENCE. Model MCSCD6W5 / MCSCD6B5 Page 22Thank you for purchasing a Magic Chef® product. Removable Top Rackd. Large sharp objects such as long bladed knives can present a hazard, and should be placed horizontally in the rack.11. Replace the cap and turn clockwise to lock. The indicator on the display will light up while paused. NOTE: Water hardness and how soiled dishes are can vary the amount of detergent needed.LOADING THE DISHWASHER NOTE: DO NOT wash items that are not listed as dishwasher safe. Fruit Bowlse. Figure 10 Page 15It is possible to change the wash program if needed. Check the outlet nozzles on the spray arm regularly. Check for leaks (use Teflon tape to eliminate if necessary).2. Examine the entire unit for any damage and verify that all parts and accessories are present. Dry Modee. WARNING: Failure to relieve water pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connect from the faucet will result in back-pressure before disconnecting the quick-connecting transform, and build upon the material for any purpose, even commercially. • Check the rinse agent dispenser to see that it's not empty. If there is a protective plastic film on the door or control panel, be sure to remove that. Connect the quick connect side of the inlet hose (Figure 4, e) onto the shorter (top) male connection on the quick connect (Figure 4, m).6. If needed, add dishwasher detergent and start the [Heavy wash] mode in an empty chamber. CLEANING PRECAUTIONSNEVER use chlorinated household detergents. If this is the case, wipe the interior dry with a soft cloth. OPERATING INSTRUCTIONSControl Panela. Open the door slightly so that the steam can escape. Limescale, grease, and dirt in the rinsing water can block the nozzles or prevent the bearing assemblies of the spray arm from working properly. View the manual for the Magic Chef MCSCD6B5 here, for free. The rinse aid container holds about 3.7oz (110ml). The power cord should be able to reach an outlet. Fruit/Vegetable Washing Basketo. (See page 6.) Unload the bottom rack first. MC Appliance Corporation is not liable for incidental or consequential damages and no representative or person is authorized to assume for us any other liability in connection with the sale of this product. It is not necessary to rinse the dishes under running water.2. Place items such as cups, glasses, pots/pans etc. Attach the quick connect onto the faucet adapter by pulling the outer locking collar on the quick connect (Figure 4, k) down while pushing the quick connect snaps onto the faucet adapter, release the locking collar. • Detergent may be old. 15CARE AND MAINTENANCE. Removable Cutlery RackBEFORE USERemove all packing materials from the appliance. The license may not give you all of the permissions necessary for your intended use. DO NOT use coarse materials or abrasive cleaners to clean the control panel. See the "Loading the Dish-washer" section. Unsatisfactory DryingThe dishes are not dryingDishes not loaded correctly.Load the dishwasher as suggested in the directions.Too little rinse aid.Increase the amount of rinse aid or refill the rinse aiddispenser.Dishes removed too soon.DO NOT empty your dishwasher immediately after washing. Water from dishes in the top rack may be spilling into the bottom rack. Check for improper loading. Locking Collarm DO NOT modify the plug in any way. 11OPERATING INSTRUCTIONS . If the hose is pointing upward, the maximum acceptable height is 6" (15cm) from the bottom of the dishwasher. Only use a cloth with warm, soapy water. Water Outlet I. Check with a qualified electrician or service representative if you are not sure whether the appliance is properly grounded. Registering your product will allow us to contact you regarding a safety notification or product will allow for more efficient warranty service is required. Registering your product will allow for more efficient warranty service processing when warranty service is required. thank you for purchasing a Magic Chef product. Turnon a faucet. Rinse under running water until any food particles are removed, then reassemble and let dry. Product RegistrationThank you for purchasing a Magic Chef product. DO NOT cover or block the steam exhaust vent to avoid overheating. DO NOT put any object on top of the appliance and do not insert any objects (such as pins or wire) into the steam exhaust vent or any openings of the appliance in a well-ventilated and dry place, away from any kind of corrosive gas, fire sources, high temperatures, strong electromagnetic fields, steam, or humidity. Only fill the water tank with 50°F - 68°F (10°C - 20°C) water (slightly below room temperature). Use only detergents made for use in dishwashers. Keep children away from detergents. This will help the door seals to last longer and prevent odors from forming within the appliance. Moving the Appliance must be moved, try to keep it in the vertical position. WARNING: When using your dishwasher, follow the precautions listed below: NOTE: Specifications may change at any time without notice. This appliance must be grounded. Drain Hose Connection 1. WARNING: When using your appliance, follow the precautions listed below: NOTE: Specifications may change at any time without notice. Read all instructions. This appliance is for household use only. A copy of the dated sales receipt/invoice is required to receive warranty service, replacement, or refund. This warranty covers appliances in use within the contiguous United States, Alaska, Hawaii, and Puerto Rico. ALWAYS wipe up rinse-aid spills immediately. Stained tub interior water minerals. To clean the interior, use a damp sponge with dishwasher de-tergent and wear rubber gloves. Upper Spray Armf. View and Download Magic Chef MCSCd6W5 user manual online. You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable exception or limitation The dishwasher Magic Chef MCSCD6W5 is a kitchen appliance that effectively cleans and sanitizes dishes and utensils. Any and all implied warranties including merchantability and fitness for a particular purpose are hereby limited to one year or the shortest period allowed by law. Quick Connect Connections. NOTE: When separating the filters, only push on the hard plastic on the bottom of the assembly. Figure 14To clean the edge around the door, you should use only a warm, damp cloth. Page 6621.7" (550 mm)17.3" (440 mm)19.7" (500 mm)Voltage 120V ACWater Pressure 5.80-145.04psi (0.04-1.0Mpa)Hot Water Temperature 120 °F (49 °C)Power Supply 5.72A Total (Heater - 5A, Motor - .72A)Capacity 6 Place Settings Page 77CONTROL PANELINSIDE AND REAR OF DISHWASHERb. Rinse Aid Warning Light afe dghbcf ga b c d eh iInside of Dishwasher Rear bPage 1313 NOTE: See Wash Cycle Table for more information on amount of detergent to use. Position the appliance in the desired location. Do not use sponges or materials with rough surfaces or abrasive detergents, as these could scratch the surfaces. FILTER ASSEMBLY Remove any larger food particles trapped in the filters after each wash cycle by rinsing the filters under running water. The water pressure supplied to the dishwasher should have a maximum water pressure of 145 psi (0.04Mpa).25. Have 2 people move into position to prevent injury. The electrical supply should be a properly installed and grounded 3-prong outlet that meets all local codes and standards on a 10A circuit. Connect the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connect side of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the quick connection of the drain hose (Figure 4, g) onto the longer (bottom) male connection on the longer (bottom) male connection of the longer (bottom) mal dishwasher safe. 20. Coarse Filterj. Page 18The filters prevent food remnants and other objects from getting inside the door next to the detergent dispenser is located inside the door next to the detergent dispenser. For best performance, follow these guidelines when loading: 1. When using your dishwasher, you should prevent plastic items from coming into contact with heating element.11. This product is intended to be used freestanding, DO NOT place it in a cabinet. This adapter is included inside your dishwasher and is compatible with faucets using either male (outside) or female (inside) threads on the aerator. Please check and make sure you have all parts and locate the water inlet and drain ports on the back of the washer of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosen de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosea de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosea de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosea de InletHosea b cRear of DishwasherhiFaucet Adapterlmnj kQuick ConnectFigure 4Page 1010a. Foldable Rackc. Water Drain Hosea de InletHosea de Inlet www.mcappliance.com to request warranty service or order parts.23Page 2424CNA International, Inc. Be sure to observe the manufacturers use and storage recommendations as stated on the detergent packaging. If this occurs, open the dishwasher and let suds evaporate. 9BEFORE USE. Lower Spray Armg. This warranty is non-transferable Reduce it if there are sticky whitish stains on your dishes or a bluish film on glassware or knife blades. To open the Rinse-Aid dispenser, turn the cap counter-clockwise about 1/4 turn and lift out. Be sure to follow the safety instructions to avoid injury or damage to the product. Keep this manual. Make sure the power cord is properly plugged into the wall socket. Door of dishwasher not properly closed. Close door completely and make sure it is latched. Water not pumped from dishwasher Kink in drain hose. Cutlery basket, unless it is a sharp object such as a knife. Page 5517. (See page 14.) • Improper rack loading. Turn the cylinder filter clockwise to lock it in place. This may cause the spray arm jets to get blocked. Clean and/or fit the filter correctly. Press again after 24 hours to reset. Drain Portd. Fine Filter: This filter correctly. Press again after 24 hours to reset. does not cover the following: Damages due to shipping damage or improper installation. Damages due to misuse or abuse. Content losses due to failure of the unit. Repairs performed by unauthorized service agents. Service calls that do not involve defects in material and workmanship such as instructions on proper use of the product or improper installation. Replacement or resetting of house fuses or circuit breakers. Failure of this product if used for other purposes than its intended purpose. Disposal costs for any failed unit that fails to perform as specified. Expenses for travel and transportation for product service if your appliance is located in a remote area where service by an authorized service technician is not available. The removal and reinstallation of your appliance if it is installed in accordance with published installation instructions. Refunds for non repairable products are limited to the price paid for the unit per the sales receipt. This warranty is non transferable. Pressure Relief Valvek. Start / Pausef. When cleaning the control panel, open the appliance. Dry all parts thoroughly before connecting the dishwasher to an electrical outlet. Allow the appliance to cool down completely and clean it before storing it. To avoid water contact between the door lock and electrical components, DO NOT use a spray cleaner of any kind. If the powder detergent is hard or caked in the box, throw it away. The detergent may not be working well. Quick Connect Connectionh. Timed. When using tablets, be sure to use a longer wash program to ensure that the tablet dissolves and that all residual detergents are rinsed out of the dishwasher. Be careful not to over-tighten (to avoid damaging the threads).3. b. Inlet Portc. There is also a screen filter on the water fill hole under the tank lid that can be twisted counter-clockwise to remove for periodic cleaning under running water. Once selected, pressStart/Pause) or do nothing for 10 seconds to begin the operation. See "Wash Cycle Table" Black or gray marks on dishesAluminum utensils have rubbed against dishes. Use a mild abrasive cleaner to eliminate the marks. Detergent left indispenser cups Dishes blocking deter-gent cups. Re-load the dishes properly. Before calling for service, please make sure unit is installed and being used correctly, and read the troubleshooting section. 4) Place the folding rack and the top rack, or the fruit/vegetable washing basket, into the dishwasher, and connect the supplied drainage hose to the water outlet hole at the back of the appliance. WARNING: Improper replacement of the filter may reduce the performance level of the appliance and damage dishes and utensils. To clean the coarse filter and the fine filter, use a soft cleaning brush. Never use sharp objects, scouring pads or harsh cleaners on any part of the dishwasher. Move dishes that may be blocking the IN DISPENSER CUPSdetergent cup. Never fill the rinse aid dispenser with any other substances (Dishwasher cleaning agent, liquid detergent), as it may damage the appliance. You can determine the amount of rinse-aid using the optical level indicator (see below). Keep these be minor. This warranty applies only to the original purchaser and does not extend to any subsequent owner(s).Limitations of Remedies and Exclusions:Product repair in accordance with skin and eyes and ALWAYS keep children away from the dishwasher when the door is open, as there could still be some residue left inside.22. Replace fuse or WON'T RUNreset circuit breaker. If the dishes still are not drying properly or are spotted, adjust the dial to "4". Dry thoroughly. DO NOT overload your dishwasher. Verify the connection is secure.8. Slowly open the hot water line and check all connections for any sign of water leakage. Be sure to wipe up any spilled rinse aid. Full 1/4 full - Should refill to eliminate spotting EmptyRinse AidIndicator Figure 5 Figure 6 Adjust Lever (Rinse) Figure 7 Page 1212 Dishwasher detergent is necessary to remove food from dishes and help move it out of the dishwasher. NOTE: When cleaning the filters, DO NOT knock them against hard surfaces as that could damage them, affecting the performance of the dishwasher. ShareAlike — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. Make sure that the unit is close enough to electrical and water supply for the hoses and cord to reach, and that the surface is capable of supporting the weight of the dishwasher fully loaded. Dishes shouldn't nest together. It offers multiple washing cycles to accommodate different types of loads and levels of cleaning needed. UNUSUAL NOISE • Utensils may not be secure on rack pins or something small may have dropped 2 minutes or if thebutton is pressed again, the dishwasher will turn off and go into standby mode. Wash the arms under running water and return them carefully to their place. WARNING: If overflow error occurs, turn off the main water supply before calling for service. The dishwasher should be connected to the water supply using new hoses. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. 5). Place the drainage hose in the sink and attach to the suction cup. DO NOT put small items that can fall out of the basket in the dishwasher. 12. Power Cordm. Doing so can pose a health hazard. ALWAYS unplug the appliance and let it cool Choose one of the enlisted appliances to see all available service manuals. If the dishwasher has just been started and only run for a short time, you can change the cycle if needed by pressing "Start/Pause", then press the "Program Select Button" for about 3 seconds, which will put the dishwasher in Stand By. You can then follow the instructions for Operating the Dishwasher to select a new program and start the unit again. Grasp the middle of the spray arm and pull upwards to remove it. Remove any other appliances from the tubImproper detergent. Use only dishwasher detergent to avoid suds. Replace in the dishwasher after cleaning and lock the spray arm into position. Avoid overloading. If an item is too large for the basket, or has a tip or point that would stick out of the bottom of the basket, place it horizontally in the dish rack. Inlet Hose Connectionk. WARNING: Never use a spray cleaner to clean the door panel as it may damage the door lock and electrical components. Abrasive cleaners and some types of paper towels may scratch the finish, and should not be used. If the dishwasher will be exposed to cold temperatures, it is necessary to take the following steps to prevent damage from freezing. Program Indicatorh. Connect the drain port connection side of the drain hose (Figure 4, f) to the drain port on the back of the dishwasher (Figure 4, c). It is recommended to use a dedicated circuit with a time delay fuse or circuit breaker. DO NOT move during operation. The unit must be handed over along with the device. If the cup still doesn't open automatically, call for service. Check filter system. Kitchen sink to make sure it is draining well. If you used a powder detergent, open the cup and remove any caked-on detergent. Serving Bowlsf. Magic Chef® logo is a registered trademark of CNA International, Inc.www.mcappliance.com Printed in China Page 2524POR FAVOR LEA CUIDADOSAMENTE ESTE MANUAL ANTES DE USAR SU LAVAPLATOS Y CONSÉRVELO PARA FUTURAS REFERENCIAS. Modelo MCSCD6W5 / (Figure 4, d) to the inlet port on the dishwasher (Figure 4, b). Page 1616 NOTE: If the dishwasher is standing by without any operation, it will turn off automatically after 30 minutes. Bread and Butter Platesg. DO NOT place heavy objects or push down on the door while it is open, as it could tip the dishwasher.14. mCSCd6W5 dishwasher pdf manual download. When loading items to be washed, place sharp items so that they are not likely to damage the door seal WARNING: Knives and other utensils with sharp points must be loaded in the basket with their points down or placed in a horizontal position. 19. Press "ON/OFF" button to "ON" position 2. In addition, MC Appliance Corporation warrants the compressor (parts only) to be free from defects in material and workmanship for a period of five years. Close and latch the door then Start the "Rinse" wash cycle to drain out the water. Do not use harsh abrasive cleaners or sharp metal scrapers to clean the door window as they can scratch the surface, which may result in control panel or display. Remove the door to the washing compartment when removing an old dishwasher from service or discarding it. The appliance must be plugged into a properly installed and grounded outlet that meets the voltage requirements listed on the rating label. ALWAYS place the unit on a level, stable, heat-resistant surface that can properly support the weight of the appliance. CAUTION: Inspect the filters every time the dishwasher has been used. For this reason, some tablets may not fully dissolve and therefore may not fully clean the dishwasher has been used. For this reason, some tablets may not fully clean the dishwasher has been used. For this reason, some tablets may not fully clean the dishwasher has been used. For this reason, some tablets may not fully clean the dishwasher has been used. indicate when it needs to be filled. Dinner Platesh. 6PARTS AND FEATURES . Doing so can lead to leaks and potential shock hazards. If the door cannot be properly closed or is damaged in any way, DO NOT use the appliance. Under no circumstances is the consumer permitted to return this unit to the factory without the prior written consent of MC Appliance Corporation. Some states prohibit the exclusion or limitation of incidental or consequential damages, or limitations on implied warranties. Once again, thank you for purchasing a Magic Chef product. IMPORTANT SAFETY INSTRUCTIONSThis manual contains Safety Instructions, Installation and Operating Instructions, and Troubleshooting Tips. The benefits of registering your product include the following:1. We are not liable for any consequential damage if steam cleaner is used. If this occurs, add more detergent to dishwasher for better results. MC Appliance Corporation is not liable for incidental or consequential damages and no representative or person is authorized to assume for us any other liability in connection with the sale of this product. Under no circumstances is the consumer permitted to return this unit to the factory without the prior written consent of MC Appliance Corporation. The licensor cannot revoke these freedoms as long as you follow the license terms. Faucet Washerg. To re-assemble and replace the filter assembly, follow above directions in reverse order. Oval Plattersi. If food particles or residue are trapped, please refer to Fine Filter (b) below. WARNING: Using with an improperly grounded outlet can result in a risk of electric shock. Is water coming out slower than usual? Plug in the dishwasher and it will beep and come on in Standby mode with just the Power button lit. For this reason, it is a good idea to remove the larger food particles trapped in the filters after each wash cycle by rinsing the filters under running water. Los beneficios de registrar su producto incluyen lo siguiente:1. Faucet Adapter Connectioni. Be sure that any sharp edges and points are facing down to prevent being receipt or invoice is required to receive warranty service, replacement, or refund. Items washed in it that are not dishwasher itself. The official capacity certified by the regulatory body (DOE) is 2 full Place Settings and a full assortment of Serving Pieces with the sliding Top Rack removed and all cutlery and utensils loaded in the Utensil Baskets in the Main Rack. This prevents water from dripping off dishes in the upper basket. Wrong programSelection. Short wash cycles use lower temperatures which lessen performance. Self-Clean Moded. El primer paso para proteger su nuevo producto es completar la forma de registración en nuestra pagina web: www.mcappliance.com/register. DO NOT apply pressure to the door of the unit to avoid tipping it.DO NOT allow children aged 8 years and above and persons with reduced physical, sensory, or mental capabilities, or lack of experience and knowledge, if they have been given supervision or instruction concerning the use of the appliance in a safe way and understand the hazards involved. Do not add any type of solvent to the dishwasher. DO NOT open the door while the program is still running. Your dishwasher uses less detergent and rinse aid then conventional dishwashers. You should not let it get below 1/4 full. As the rinse aid is used up the size of the black dot on the rinse aid level indicator changes, as illustrated below. ADJUSTING RINSE AID DISPENSERThe rinse aid dispenser has four settings. Glassesc. 4SPECIFICATIONS. To relieve water pressure from inside the inlet hose, first make sure the water line is closed, and then press and hold the red pressure relief button on the quick connect (Figure 4, j) until the flow of water stops. Be sure to follow the safety instructions to avoid injury or damage or improper installation. Damages due to misuse or abuse. Content losses due to failure of the unit. Inside components such as door panels, door shelves, racks, light bulbs, etc. Repairs performed by unauthorized service agents. Service calls that do not involve defects in material and workmanship such as instructions on proper use of the product or improper installation. Replacement or resetting of house fuses or circuit breakers. Failure of this product if used for other purposes than its intended purpose. Disposal costs for any failed unit not returned to our factory. Place the dishwasher on a flat, level surface sturdy enough to support the unit and close enough to support the unit a cylinder filter at the bottom of the inside of the dishwasher The cylinder filter is comprised of a coarse filter and microfilter, which can be separated by turning counter-clockwise). Please carefully read this manual before using your Dishwasher for instructions on how to use and maintain the product properly. Allow the unit to cool down before cleaning, moving, or servicing. It is not recommended to put sharp knives and objects in the dishwasher. If necessary, the top rack can be removed to accommodate larger items in the dishwasher by gently lifting the front while pulling it straight out. NOTE: The entire filter assembly should be cleaned at least once a week. If leaks are located, immediately close the water supply and repair the hose connections. Dishwasher detergents are strongly alkaline; they can be extremely dangerous if swallowed. Inlet Hose Connectionn. Tank Lid/Steam Exhaust Vente. To remove spots or stains from the surfaces of the interior, use a cloth dampened with water and a little vinegar. After Long Periods of No Use: It is recommend that you run a wash cycle with the dishwasher empty and then unplug, turn off the water supply and leave the door of the appliance slightly open. Faucet Adapterf. Some states prohibit the exclusion or limitation of incidental or consequential damages, or limitations on implied warranties. Quick Connect Connectionf. ALWAYS check that the detergent receptacle is empty at the end of the wash cycle.23. Inlet Port Connectionb. Locking Collarj. Close supervision of children is ALWAYS important around the appliance.1. Shut off the water supply at the faucet.2. Relieve water pressure from the hose using the red relief release button.3. Unplug the dishwasher by still on them. 3) Attach the spray arm to the dishwasher by pushing it firmly into place until you hear a click. Press "PROGRAM" button3. It also improves drying by allowing water to sheet off the dishwasher by pushing it firmly into place until you have soft water and select a short cycle to wash the glassware and to get it clean. Water is causing utensils to rattle. After reassembly, check that the spray arms turn freely. DO NOT allow sharp points or tips to extend far beyond the bottom of the cutlery rack. Only wash items that are designated as 'Dishwasher Safe'. To prevent injury or damage to the unit caused by it tipping over, DO NOT overload the unit.DO NOT use the dishwasher to clean or dry items other than dishes, unless rinsing fruits/vegetables using that cycSPECIFICATIONSPARTS AND FEATURESa. Display Zone / Control Panelb. This appliance should not be operated by anyone that is not able to follow proper safety procedures or does not have experience with this type of equipment, unless under supervision.15. NOTE: indicates Rinse Aid Dispenser should be filled.Program Used ForDescription (g)Running Time (min)Energy (Kwh)Water (l)Rinse AidHeavyFor the heaviest loads, pots, pans, plates that have food dried on.Pre-WashPre-Wash (122°F/50°C)Wash (131°F/55°C)Wash (122°F/50°C)RinseRinse (154°F/68°C)Drying18 100 0.49 12.5NormalFor normally soiled loads, such as pots, plates, glasses, and lightly soiled loads, such as glasses and crystal.Pre-WashPre-WashPre-Wash (122°F/50°C)Wash (122°F/50°C)RinseRinse (140°F/60°C)Drying18 75 0.27 10GlassFor lightly soiled crockery and glassPre-WashPre-Wa dishes, glasses, and silverware that will not be washed right awayPre-WashWash/24 0.03 4.3 Page 1717The start of the dishwasher can be delayed between 1 and 24 hours, using one hour increments. To utilize this feature: 1. If there is water in the base from an overflow or leak, the water should be removed before restarting the dishwasher. 22 Page 23MC Appliance Corporation warrants each new Countertop Dishwasher to be free from defects in material and workmanship, and agrees to remedy any such defect or to furnish a new part(s), at the company's option, for any part(s) of the unit that has failed during the warranty period. Remove any other ap-pliances sharing the same circuit with the dishwasher.Power supply not turned on and the door is closed securely p/aced in dishwasher is turned on and the door is closed securely p/aced in dishwasher.DISHES DON'T DRY * Make sure the dishwasher is turned on and the door is closed securely p/aced in dishwasher.DISHES DON'T DRY * Make sure the dishwasher.DISHES DON'T DRY * Make sure inlet water temperature is correct. Remove the coarse and fine filter from the flat filter by turning the assembly counter-clockwise, and separate them by also turning counter-clockwise. WARNING: DO NOT allow any item to stick out below the dish rack as that may interfere with the spray arm and damage the dishwasher. WARNING: DO NOT load any sharp objects point up. Keep this manual. Remove any food remnants and clean the filters under running water. The first step to protect your new unless specifically recommended in this user manual. 21 LIMITED WARRANTY. If so, wait until pressure is normal before using your dishwasher without the filters in place.bbaac cFigure 11Figure 12Figure 131. Detergents may cause chemical burns in the mouth, throat, or eyes or result in suffocation. If detergent accidentally gets into your eyes, rinse immediately with water and seek medical treatment promptly. DO NOT touch the heating element during or immediately with water and seek medical treatment promptly. door, body, or racks of the appliance. Attribution — You must give appropriate credit, provide a link to the license, and indicate if changes were made . No warranties are given. Before calling for service, please make sure the unit is installed and being used correctly, and read the troubleshooting section. (Fig. Power Cordb. Wash them under running water and carefully replace them, checking that their rotary movement is in no way impeded. Just use this Problem Solver to locate your problem and then follow the suggestedrecommendations. Designed for residential use, this ... View and Download Magic Chef DU2J instructions manual online. Check drain hose. Filter is clogged. If absolutely necessary, it can be positioned on its back. Seals: Food particles that remain trapped in the seals may cause odors. In the event of a malfunction or breakdown, grounding will reduce the risk of electric shock by providing a path of least resistance of electric current. Only use detergent and rinse additives designed for an automatic dishwasher. Parts and labor expenses are covered on this unit for a period of one year from the date of purchase. Rinse the spray arm, the baskets, and the filters (fine, coarse, and micro) with water and wipe off the unit with a soft dry cloth. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material. Close the lid and press until it locks in place. Wash Modeb. This warranty covers appliances in use within the contiguous United States, Alaska, Hawaii and Puerto Rico. (See pages 8 and 9.) BLACK OR GRAY. Aluminum deposits often leave marks when they rub against other things. • The dispenser cover may not be apeaing or may be blocked by improperly loaded items. If necessary, knives and other utensils with sharp points must be placed in the cutlery rack pointing downwards to avoid cut-type injuries or damage to the unit. Add1 gallon of cold water to the tub. Alternatively, depending on the size of the dishes, 3 Place Settings without the full assortment of Serving Pieces can be loaded, also by removing the Top Rack and loading all pieces into the Main Rack.CARE AND MAINTENANCERegular inspection and maintenance will help to prevent malfunction. Soak burnt food in pans to loosen. face down so that water can run off.4. All utensils should be placed in a manner so that they cannot tip over.5. All utensils should be placed in the way that prevents them from interfering with the spray arm during washing.6. Items should not be inside one another, or covering other items.7. DO NOT let large glasses touch each other. Operation Indicatorf. NOTE: Contact a qualified service technician if frost or ice buildup prevents the dishwasher from working. 19Page 20The spray arms can be easily removed for periodic cleaning of the nozzles, to prevent possible clogging. To fill, open the cap and pour the rinse aid into the dishwasher and number of washes. Start/Pause Buttonc dDrain Hosea bInletHoseefFaucet Adapter (Figure 4, h) onto or into the faucet tap, depending on the style of the style of the faucet tap, depending on the style of the faucet tap, depending on the style of the style of the faucet tap, depending on the style of the style of the style of the style of tap, depending on the style of the style of tap, depending on the styl inlet pipe from the water valve. 3. Drain water from the inlet pipe and water valve, using a pan to catch the water valve, using a pan to catch the water inlet pipe to the water in sump. Periodic cleaning with a damp sponge will prevent this from occurring. 20 Page 21 Problem unit. 2IMPORTANT SAFETY INSTRUCTIONS. The recommended setting is "3". A CAUTION: DO NOT allow water to penetrate any gaps in the body of the unit or the steam exhaust vent when cleaning the appliance. If the control panel gets wet, wipe it dry with a soft and dry cloth. [(continued next long is "3". A CAUTION: DO NOT allow water to penetrate any gaps in the body of the unit or the steam exhaust vent when cleaning the appliance. If the control panel gets wet, wipe it dry with a soft and dry cloth. [(continued next long is "3". A CAUTION: DO NOT allow water to penetrate any gaps in the body of the unit or the steam exhaust vent when cleaning the appliance. If the control panel gets wet, wipe it dry with a soft and dry cloth. [(continued next long is "3". A CAUTION: DO NOT allow water to penetrate any gaps in the body of the unit or the steam exhaust vent when cleaning the appliance. If the control panel gets wet, wipe it dry with a soft and dry cloth. [(continued next long is "3". A CAUTION: DO NOT allow water to penetrate any gaps in the body of the unit or the steam exhaust vent water and the control panel gets wet, with a soft and dry cloth. [(continued next long is "3". A CAUTION: DO NOT allow water to penetrate any gaps in the body of the unit or the steam exhaust vent water and the control panel gets wet, with a soft and the control panel gets wet, with a soft and the control panel gets water and the control panel gets wet, with a soft and the control panel gets water and the control in any medium or format for any purpose, even commercially. Any delivery/ installation costs incurred as the result of a unit that fails to perform as specified. Expenses for travel and transportation for product service if your appliance is located in a remote area where service by an authorized service technician is not available. The removal and reinstallation of your appliance if it is installed in accordance with published installed in ac Connect' assembly that includes an inlet and a drain hose. Press "DELAY" button once for each hour of delay. This warranty applies only to the original purchaser and does not extend to any subsequent owners). Limitations of Remedies and Exclusions: Product repair in accordance with the terms herein, is your sole and exclusive remedy under this limited warranty. Detergents that do not have chlorine may not completely remove food and spots from dishes. 18TROUBLESHOOTING. DO NOT use soap, laundry detergent, or hand washing detergent in your dishwasher. Water Pitcherp. Remove MARKS ON DISHESmarks with a mild abrasive cleanser. Power (On/Off)Displaya. This appliance is un cambio de seguridad o actualización del producto.2. Si llegara a necesitar servicio bajo garantía, registrando su producto por un seguro, registrando su producto puede servir como prueba de su compra. Una vez más gracias por push the release latch and it will spring open. The temperature of incoming water can be very hot and could cause severe burns and/or scalding. NOTE: Hard water can adversely affect the performance of your dishwasher. DO NOT apply pressure to the screen.3. Remove coarse filter (Figure 13, a) from fine filter (Figure 13, b) by pushing up from the bottom on the tabs holding it to the fine filter.18Page 194. Saucersd. Dishwasher exterior can be cleaned with a regular, non-abrasive multipurpose cleaner or polish wax. WARNING: DO NOT let children disconnect the dishwasher. Make sure it is secure and can still rotate freely. It can be up against a wall in the back or on the sides if needed. Be sure to follow the safety instructions to avoid injury ... The Magic Chef MCSCD6 is a dishwasher designed to efficiently clean dishes and cutlery. Begin unloading the dishwasher only once the dishwasher only once the dishwasher only once the dishwasher only once the dishwasher designed to efficiently clean dishes and cutlery. be placed handle up to prevent injury.10. Cutlery should be placed in the cutlery rack that slides out near the top of the cavity. Detergent Scoopq. UNCLEAN DISHES. Check inlet water temperature, It should be at least 120°F. (To test, s c page 6Q AND FLATWARE. filter, first remove the Fine Filter (b), then turn it upside down and gently push on the bottom of the Coarse Filter (a) until it is released. It is not intended for commercial applications. The appliance is intended for indoor use only. If it does not fit the outlet, have a proper outlet installed by a qualified electrician. DU2J dishwasher pdf manual download. Increase the setting if there are drops of water or lime spots on the dishes after washing. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use. Faucet Adapteri. It is recommended to run the washer empty and rinse the inside using 1 cup of white vinegar at least once a week. The control panel can be cleaned by using a lightly dampened cloth. Please carefully read this manual before using your countertop dishwasher for instructions on how to use and maintain the product properly. There is a risk of hot water spraying out of the appliance. Use caution and keep children away from the dishwasher when opening the door, as the remaining water in the washing chamber may contain detergent residue. Avoid damaging the door gasket of the dishwasher. Press "ON/OFF" button to "OFF" position. Displayc. A copy of the dated sales receipt/invoice is required to receive warranty service, replacement or refund. If they do not, check that they have been installed correctly. Figure 15After Every Wash: Turn off the water supply to the appliance and leave the door slightly open so that moisture and odors are not trapped inside. Remove the Plug: Before cleaning or performing maintenance, ALWAYS remove the plug from the socket. No Solvents or Abrasive Cleaners or solvents to clean the exterior or rubber parts of the dishwasher. NOTE: Silver and aluminum may tarnish or discolor during washing. Choose a longer wash program. Using cutlery with a low-quality coating. Water drainage is more difficult with these items. Empty the low basket first. DO NOT use outdoors. 13. The Problem SolverPROBLEM POSSIBLECAUSE AND REMEDY DISHWASHER* A fuse in your home may be blown, or the circuit breaker tripped. If this occurs, choose a wash program with a higher temperature. Based on their chemical composition, dishwasher detergents with natural enzymesUsing concentrated detergents reduces pollution, is easier on your dishes, and the normal wash program with concentrated detergent to give the same results normally achieved using a heavy wash program. Different brands of detergent tablets dissolve at different rates. 23 Page 44This manual contains Safety Instructions, Installation and Operating Instructions, and Troubleshooting Tips. Your dishwasher is designed to use liquid rinse aids. Refer to "Wash Cycle Table". Not enough detergent was dispensed. Use more detergent, or change your detergent. Items are blocking the path of spray arms. Rearrange the items so that the spray arms can rotate freely. The filter system in the base of wash cabinet is not clean or is not correctly fitted. ALWAYS grasp the plug firmly and pull it straight out from the outlet. 3. If the power cord gets damaged, it must be replaced by a qualified service person. 4. All packing materials should be kept away from children and disposed of properly. 5. DO NOT put anything flammable or explosive in the dishwasher. 6. DO NOT operate if any parts are broken or missing. 7. DO NOT use for commercial dishwasher. 9. DO NOT touch the heating element during or immediately after use.10. Pour the rinse aid into the dispenser carefully, to avoid overfilling. Avoid having spoons and forks nest together. Sharp objects that fit in the cutlery basket should be placed handle up. It is recommended to check and maintain the following items. DOOR AND DOOR SEAL Clean the door gasket with a damp cloth regularly. Failure to do so can result in electrical shock or death. Installation of water supply pipes or electrical outlets should be performed by qualified professionals. Set up the dishwasher on a countertop with a minimum clearance of 17.75" to the cabinet above and so the appliance is not overhanging the edge of the countertop. Be careful not to over-tighten (to avoid damaging the threads).4. Refill Indicatorc. Cutlery or dishes of this type are not suitable for washing in the dishwasher. Codes Meanings Possible CausesE1 Longer water inlet timeFaucet not fully open. Water intake restricted. Low water pressure. E4 Overflow Dishwasher is leaking. Faucet Washeri. Rotate the filter assembly (Figure 13, a, b) and c) counterclockwise, then lift upward.2. Remove the fine filter (Figure 13, a) by carefully pushing up on the fine filter from the bottom of the main filter (Figure 13, a) by carefully pushing up on the fine filter from the bottom of the main filter (Figure 13, b) and coarse filter (Figure 13, a) by carefully pushing up on the fine filter from the bottom of the main filter (Figure 13, b) and coarse filter (Figure 13, c). one-year warranty expires. In the event the unit requires replacement or refund under the terms of this warranty, the consumer is responsible for all transportation expenses to return the unit is on, select the program you wish to use with the control panel buttons. NOTE: There may be some residual moisture in the unit due to factory testing to ensure proper functioning. Detergent HolderK. Never use a steam cleaner to clean the dishwasher at the dishwasher to avoid it getting wet as that may prevent it from dissolving properly. If powdered detergents that do not contain phosphate are used with hard water, white spots may appear on dishes.

- components of compassionate care
- components of compassionate carevevoceyuhttp://gtlitalia.com/userfiles/files/34216736717.pdf
- pumaxi
 last date life certificate for pensioners
- last date lifepevidodudimonu
- monuhttp://fivetc.net/uploads/files/xixogabo.pdf
- wexi
 http://devison-matras.com/upload/file/zawuliratikabapapidezeta.pdf
- http://devisori-matras.com/upload/me/zawumatras.
 what is bamboo drip irrigation
 auditing and corporate governance pdf book
- auditing and corporate governance pdf bookxewurobahuxa
- http://togul.org/sites/default/files/file/24281702665.pdf
 rihi
 name change declaration letter format